

Express Mailing Label No.: ET580099230US

PATENT APPLICATION

Docket No.: 1300.2.6

IBM Docket No.: BLD920010020US1

UNITED STATES PATENT APPLICATION

of

Jennifer Q. Trelewicz

for

RASTER DATA COMPRESSION APPARATUS AND METHOD

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181

RASTER DATA COMPRESSION APPARATUS AND METHOD

BACKGROUND OF THE INVENTION

1. The Field of the Invention

The present invention relates to the field of data compression and more particularly, to the field of lossless compression and decompression of bi-tonal raster data.

2. The Relevant Art

Raster data is generated by graphical systems when converting graphical objects into a low-level bitstream appropriate for display and rendering. The generated bitstream is often bandwidth and processor intensive, especially in light of the push for systems with higher resolutions and faster rendering speeds. Many graphical systems and products such as page printers, phototypesetters, and electrostatic plotters have dedicated hardware with specialized and often costly architectures optimized for processing the large amounts of graphical data at high speeds.

While image quality and raster data processing requirements continue to increase, market demand for image-oriented devices and systems has proven to be particularly price sensitive. Manufacturers of these devices and systems are under constant pressure to deliver higher resolution systems at lower prices. As a result of these pressures, product life cycles have been dramatically shortened.

Shortened product life cycles make it difficult for manufacturers to recoup the tooling and marketing costs associated with the introduction of new products. Cost-effective components are leveraged to their maximum capacity and performance. Existing devices and systems often have little bandwidth or processing capacity available for new features or enhancements. Ideally, additional features and enhancements must fit within the constraints of existing products and thereby increase their product life cycle at no additional materials cost.

1 Compression and decompression of raster data offers the hope of reducing the
2 bandwidth requirements at a given rendering resolution and increasing the data throughput
3 and rendering resolution attainable over fixed-bandwidth channels. However, compression
4 algorithms are typically complex and require large amounts of memory and processing
5 power. Large dictionaries of reference data or complex mathematical formulas may be used,
6 each of which requires significant computational resources. Compression algorithms often
7 process a relatively large context of data surrounding a data element in order to spot
8 redundancies or patterns within the raster data. Processing large amounts of data increases
9 both the memory requirements and the processing requirements of compression systems.

10 From the above discussion, it can be seen that it would be beneficial to improve the
11 performance of graphical systems and other data-intensive systems by providing an apparatus
12 and method for compressing and decompressing data using minimal processing resources.
13 Minimizing the complexity of compressing and decompressing data facilitates handling
14 more data with lower cost components. Low complexity compression also facilitates adding
15 additional capability to existing products and systems at little or no additional cost.
16
17
18
19
20
21
22
23
24
25
26

OBJECTS AND BRIEF SUMMARY OF THE INVENTION

The apparatus and method of the present invention have been developed in response to the present state of the art, and in particular, in response to the problems and needs in the art that have not yet been fully solved by currently available raster data compression and decompression systems and methods. Accordingly, it is an overall object of the present invention to provide an improved method and apparatus for raster data compression and decompression that overcome many or all of the above-discussed shortcomings in the art.

To achieve the foregoing object, and in accordance with the invention as embodied and broadly described herein in the preferred embodiments, an apparatus and method for data compression and decompression are provided that significantly decrease raster data bandwidth requirements while consuming little processing resources. In the described embodiment, compression of raster data will be described, but it is contemplated that any type of suitable data could be compressed under the present invention.

The raster data compression apparatus in accordance with the invention comprises a number of pattern detection modules. Each pattern detection module detects and losslessly represents a particular type of pattern such as solid patterns, edge patterns, and half-tone patterns. A pattern selection module receives a stream of raster data where redundant patterns are detected and selects the best lossless representation according to particular criteria such as storage compactness. In some cases, the pattern selection module may select the original raster data, referred to as "verbatim" raster data, as the best lossless representation.

A packet formatting module packs a number of iterations of compressed data including a pattern identifier into a packet comprising a packet header and packet data. The packet formatting module is preferably configured to select the best binary representation of the compressed data for a particular application.

1 Once a packet of data has been compressed and formatted it may then be transmitted
2 or stored efficiently. Upon receipt or retrieval, a raster data decompression apparatus and
3 method of the present invention may deformat and uncompress the raster data.

4 The raster data decompression apparatus preferably includes a pattern decoding
5 module and one or more pattern generation modules and may include a packet deformatting
6 module. The packet deformatting module works in conjunction with the formatter to use the
7 best binary representation of the compressed data for a particular application. The packet
8 deformatting module unpacks a number of iterations of compressed data including the
9 pattern identifier from a packet header and associated data.

10 After the deformatting module unpacks data, the pattern decoding module uses the
11 pattern identifier to activate the appropriate pattern generator. Each pattern generation
12 module generates a particular type of pattern such as solid patterns, edge patterns, and half-
13 tone patterns from a corresponding lossless representation, i.e., the pattern data. In addition
14 to the pattern generators, the pattern decoding module may activate a verbatim data transfer
15 module which simply receives and provides the original data in verbatim i.e. uncompressed
16 form.

17 These and other objects, features, and advantages of the present invention will
18 become more fully apparent from the following description and appended claims, or may be
19 learned by the practice of the invention as set forth hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the manner in which the advantages and objects of the invention are obtained will be readily understood, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

Figure 1 is a schematic block diagram illustrating a print system in accordance with the present invention;

Figure 2 is a schematic block diagram illustrating one embodiment of a printer in accordance with the present invention;

Figure 3 is a schematic block diagram illustrating one embodiment of a raster compression system in accordance with the present invention;

Figure 4 is a schematic block diagram illustrating one embodiment of a raster compression module of the present invention;


Figure 5 is a table illustrating example bi-tonal raster patterns in accordance with the present invention;

Figure 6 is a schematic flowchart diagram illustrating the operation of one embodiment of a raster compression method of the present invention;

Figure 7 is a schematic block diagram illustrating one embodiment of a raster packet formatting module of the present invention;

Figure 8 is a schematic flowchart diagram illustrating one embodiment of a raster packet formatting method of the present invention;

Figure 9 is a set of tables illustrating various raster packet formats in accordance with the present invention.



1 Figure 10 is a schematic block diagram illustrating one embodiment of a raster
2 packet deformatting module of the present invention;

3 Figure 11 is a schematic flowchart diagram illustrating the operation of one
4 embodiment of a raster packet deformatting method of the present invention;

5 Figure 12 is a schematic block diagram illustrating one embodiment of a raster
6 decompression module of the present invention;

7 Figure 13 is a schematic flowchart diagram illustrating the operation of one
8 embodiment of a raster decompression method of the present invention;

9 Figure 14 is a schematic flowchart diagram illustrating the operation of a further
10 embodiment of a raster decompression method of the present invention;

The figure consists of ten rectangular panels arranged horizontally, each showing a different developmental stage of a larva. From left to right, the stages are:

- Fertilized egg**: Shows a single cell with a prominent nucleus.
- 2-cell stage**: Shows two cells joined together.
- 4-cell stage**: Shows four cells in a square arrangement.
- 8-cell stage**: Shows eight cells in a more complex arrangement.
- Morula stage**: Shows a solid ball of many small cells.
- Gastrula stage**: Shows three distinct layers of cells.
- Neurulation stage**: Shows the formation of a neural tube.
- Tail bud stage**: Shows a developing tail at the posterior end.
- Hatched larva**: Shows a fully formed larva with a head, body, and tail.
- Larval stage**: Shows a more advanced larval form.

BRIAN C. KUNZLER
ATTORNEY AT LAW
10 WEST 100 SOUTH, SUITE 425
SALT LAKE CITY, UTAH 84101

27

25

26

1 facilitates a serial execution model typical of conventional software systems. Those skilled
2 in the art will appreciate that a variety of invocation mechanisms may be used in
3 computational and control systems and that a schematic flowchart need not be sequentially
4 executed or executed in the same order to be a valid embodiment of an algorithm or process.

5 Referring to Figure 1, a print system 100 illustrates a representative context for the
6 present invention. The print system 100 includes a number of workstations 102 and servers
7 104 interconnected with a LAN 106. One of the servers 104 is also a print server or host
8 108. The print server 108 serves as a host for a printer 110. The printer 110 includes a print
9 controller 112 and a print mechanism 114.

10 The users on the workstations 102, and various software tasks running on the servers
11 104, may generate print jobs that are sent to a print spooler 116 running on the print server
12 108. The print spooler 116 is typically a software process or thread running in conjunction
13 with an operating system. The protocols and formats for specifying and sending the print
14 jobs to the print spooler 116 may be operating system-dependent. The print spooler 116
15 provides means for controlling access to the printer 110.

16 The printer spooler 116 receives and queues various print jobs and typically provides
17 at least one page of print data at a time to the print controller 112 within the printer 110 via
18 a host connection 118. Typically, the print controller 112 receives pages in the form of a
19 page description language such as IPDS, Postscript, PCL, or the like. The print controller
20 112 in turn converts the page descriptions into a low-level bitstream appropriate to control
21 the print mechanism 114. The mechanism interface 120 provides the communication
22 channel between the print controller 112 and the print mechanism 114.

23 Figure 2 illustrates the interaction of the print controller 112 and the print
24 mechanism 114 in greater detail. The print controller 112 includes a rasterizer 210. The
25 rasterizer 210 converts bitmap objects referenced by the page description into a raster stream
26 212. The raster stream 212 contains data elements corresponding to pixels.

27

1 The raster stream 212 is received by a component interface controller 220 and is
2 transmitted to a mechanism interface controller 230 via the mechanism interface 120. In the
3 depicted embodiment, the printer 110 is a multi-component printer, and the component
4 interface controller 220 receives separate streams for four different colors such as cyan,
5 magenta, yellow, and black. The component interface controller 220, the mechanism
6 interface 120, and the mechanism interface controller 230 are partitioned into four subunits
7 or channels to handle the raster streams for the various components.

8 Figure 3 illustrates one embodiment of a raster compression system 300 of present
9 invention. The raster compression system 300 includes a CIC card 220 in electrical or
10 optical communication with a MIC card 230. In the depicted embodiment, the CIC card is
11 shown including a raster compression module 310 and a packet formatting module 312. The
12 MIC card 230 is shown including a raster decompression module 320 and a packet
13 deformating module 318. In the depicted embodiment, the raster compression system 300
14 receives a raster stream 212 of raster data that is preferably bi-tonal. The raster stream 212
15 may be associated with a print component such as cyan, magenta, yellow or black. For
16 example, the raster data may toggle the print mechanism between printing and not printing,
17 thus selecting between the print component and a background color such as white.

18 The raster compression module 310 reduces the bit rate of the raster stream 212a and
19 provides a compressed raster stream 314 to the packet formatting module 312, which formats
20 the compressed raster stream 314 into packets for transmission or storage. A resulting
21 packetized, compressed raster stream 316 is transmitted in one embodiment over the
22 mechanism interface 120 of Figure 2. After transmission or storage, depending upon the
23 application, the packet deformating module 318 receives the packetized, compressed raster
24 stream 316 and depacketizes it. The compressed raster stream 314 is then sent to the raster
25 decompression module 320. The raster decompression module 320 in turn converts the
26 lower bit rate compressed raster stream 314 to the raster stream 212b. The compression and
27 decompression conducted by the raster compression system 300 is lossless in that the data

1 within the raster stream 212a is identical to the data within the raster stream 212b. Non-
2 raster data such as control information may be sent over the mechanism interface 120
3 separate from the raster stream 212 or the compressed raster stream 314.

4 One objective of the raster compression system 300 is to increase the rate at which
5 data can be rendered by the printer 110 without necessarily increasing the transfer rate of the
6 mechanism interface 120. Another objective is to minimize the amount of processing
7 required by the component interface controller 220 and the mechanism interface controller
8 230.

9 Referring now to Figure 4, one embodiment of a raster compression module 310 of
10 the present invention includes a set of pattern detection and extraction modules 410, a
11 verbatim data transfer module 420, and a pattern selection module 450. The pattern
12 detection and extraction modules 410 receive the raster stream 212 and provide an attribute
13 stream 430. The verbatim data transfer module 420 receives the raster stream 212 and
14 provides a verbatim data stream 440. The pattern selection module 450 receives the attribute
15 stream 430 and the verbatim data stream 440. In turn, the pattern selection module 450
16 transmits data for a pattern identifier stream 460 and a pattern data stream 470. The order
17 in which detection, extraction, and selection occurs is not fixed, and may be conducted in an
18 order other than that given here by way of example.

19 The pattern detection and extraction modules 410 detect patterns within data
20 elements of the raster stream 212 in a manner that is preferably context insensitive in that
21 little or no state information is retained between data elements. As a result of being context
22 insensitive, the complexity of the pattern detection and extraction modules is greatly reduced.
23 Context insensitivity also allows a raster stream to be processed in a single pass.

24 The width of each data element may be platform or application independent. When
25 embodied as software, the width of the data element is preferably the word width of the
26 processor the software is executed on. Using the native word size facilitates small machine
27 code footprints for the pattern detection and extraction modules 410. Context insensitivity

1 and using the native word size also increases the frequency of cache hits and look-ahead
2 cache hits when executing the pattern detection and extraction modules 410.

3 When embodied as hardware, the width of the data element may be selected
4 according to available resources. The context insensitivity of the pattern detection and
5 extraction modules 410 reduces the need for state registers and complex control circuits.
6 Context insensitivity also facilitates a wide range of hardware embodiments including the
7 option to be highly pipelined.

8 The architecture of the raster compression module 310 facilitates a wide range of
9 embodiments. Pattern detection and extraction modules may be added or removed without
10 significantly affecting the other modules. In the depicted embodiment, shown by way of
11 example, pattern detection and extraction modules for solid patterns (410a), edge patterns
12 (410b) and half-tone patterns (410c) are included.

13 The pattern detection and extraction modules 410 are configured to detect the
14 occurrence of selected patterns within a data element of the raster stream 212 and extract a
15 set of essential attributes sufficient to losslessly represent the data element in a compressed
16 form. The essential attributes along with an indication of detection are provided to the
17 attribute stream 430. The bitwidths of the essential attributes provided by each pattern
18 detection and extraction module 410 need not be the same. Some pattern detection and
19 extraction modules may detect only a single pattern and need not provide any essential
20 attributes.

21 The verbatim data transfer module 420 receives data elements within the raster
22 stream 212 and provides those elements in "verbatim" or identical form to the verbatim data
23 stream 440. The verbatim data stream essentially provides a "worst case" or default lossless
24 representation. The pattern selection module 450 chooses the most appropriate lossless
25 representation from those that are provided by the pattern detection and extraction modules
26 410 and the verbatim data transfer module 420.

1 The inclusion of the verbatim data transfer module 420 provides the raster
2 compression module 310 with the option of transmitting data without compressing. In some
3 embodiments and applications this may frequently be necessary. The criterion used by the
4 pattern selection module 450 for selecting the most appropriate lossless representation may
5 be application dependent, but as a general rule the criterion used within the raster
6 compression module 310 is compactness (*i.e.* the lossless representation with the fewest
7 number of data bits).

8 Figure 5 illustrates representative example patterns processed by the raster
9 compression module 310. The first column corresponds to particular examples of data
10 elements within the raster stream 212. The second column shows human readable labels of
11 patterns located within the raster stream 212 by the pattern detection and extraction modules
12 410. The third column shows human readable labels applied to the examples of data from
13 the pattern data stream 470, and may be provided by the pattern selection module 450. The
14 fourth column shows an actual binary pattern that may be used to represent data from the
15 pattern data stream 470.

16 The first row (neglecting the title row) represents a data element within the raster
17 stream consisting of all ones (*i.e.* 111111111111111) that is received by the detection and
18 extraction modules 410. A pattern is detected that corresponds to a pattern identifier of
19 'solid' and pattern data of 'ON', that may be represented by a binary encoding such as a
20 single one bit. In the second row, a data element consisting of three 1's followed by zeros
21 (*i.e.* 1110000000000000) is received, and a pattern is detected that corresponds to a pattern
22 identifier of 'Edge' and pattern data of 'OFF AT BIT 3', where 'OFF AT BIT 3' is
23 represented by a binary encoding such as 00011.

24 In the third row, the data element 1110011111100111 is received, and a pattern is
25 selected that corresponds to a 'Half-tone' pattern identifier and pattern data of '75% Gray',
26 where '75% Gray' is represented with an actual pattern index such as 110000. The pattern
27 data for half-tone patterns is preferably a pattern index or code corresponding to the index.

1 In the last row, the data element of 1011010000110101 is received and represents data
2 elements not fitting into other selected patterns. Accordingly, the verbatim data pattern is
3 selected, and the data element is represented as verbatim raster data of 1011010000110101.

4 The illustrated patterns are preferably selected with an emphasis on low complexity.
5 Low complexity translates to high performance (i.e. throughput) using minimal resources
6 such as memory, processing cycles, logic gates or the like. The resulting compressed raster
7 stream thus reduces the bandwidth and storage requirements associated with raster data.

8 Figure 6 is a schematic flowchart diagram illustrating the operation of one
9 embodiment of a raster compression method 600 which in one embodiment is a method of
10 operation of the raster compression module 310. Thus figure 6 will be described with
11 reference to the structure of Figures 3 and 4 but, of course, may be practiced independent of
12 the structure of Figures 3 and 4.

13 The raster compression method 600 starts 605, after which a data element from the
14 raster stream 212 is received 608. The method 600 then detects 610 whether the received
15 data element corresponds to a first pattern, comprising in the depicted embodiment a solid
16 pattern. The detection 610 is in one embodiment conducted by the solid pattern detection
17 and extraction module 410a. If a solid pattern such as "all zeros" or "all ones" is detected,
18 a set of essential attributes representing the solid pattern is extracted 612 and selected 645
19 to provide a lossless representation of a data element from the raster stream 212.

20 If no solid pattern is detected, the raster compression method 600 proceeds to detect
21 620 whether the received data element corresponds to a second pattern. In the depicted
22 embodiment, the second pattern is an edge pattern and the detection 620 is conducted by the
23 edge pattern detection and extraction module 410b. If an edge pattern is detected, a set of
24 essential attributes such as edge position and direction are extracted 622 and selected 645.

25 If no edge pattern is detected, the raster compression method 600 proceeds to detect
26 630 whether the received data element corresponds to a third pattern. In the depicted
27 embodiment, the third pattern is a half-tone pattern and the detection 630 may be conducted

1 by the half-tone pattern detection and extraction module 410c. If a half-tone pattern is
2 detected, a set of essential attributes such an index corresponding to the half-tone pattern is
3 extracted 632 and selected 645.

4 Many half-tone patterns are possible within various systems. However, the number
5 of half-tone patterns actually used within a given system is preferably quite small. The set
6 of half-tone patterns detected and extracted by the raster compression method 600
7 specifically, and the raster compression module 310 generally, is preferably predetermined
8 and selected for a particular system or application. Dynamic methods for building
9 codebooks are possible but are not preferred in that the additional complexity is counter to
10 the objectives of the raster compression module 310.

11 A transfer 642 of verbatim data is activated when no particular pattern is detected
12 in a raster data element. The transfer 642 of verbatim data provides a lossless representation
13 that is the same as the original uncompressed raster data element.

14 In one embodiment, an appropriate set of essential attributes is selected 645 in
15 response to the extracting 612, 622, or 632 and provides a lossless representation in the form
16 of the pattern data stream 470. When selected 645, a pattern identifier such as that found in
17 the pattern identifier stream 460 is also provided. The data within the pattern identifier
18 stream 460 indicates which set of essential attributes was selected to provide the pattern data
19 stream 470.

20 In the depicted embodiment, the detecting 610, 620, and 630 are prioritized in a
21 particular activation order resulting in only one pattern extraction or the transfer 642 being
22 activated for each data element. In a further embodiment, the raster compression method 600
23 activates the detecting 610, 620, and 630 simultaneously.

24 With simultaneous activation, the select 645 must arbitrate between and select the
25 most appropriate lossless representation when more than one lossless representation is
26 possible. The criteria used by the select 645 for selecting the best lossless representation
27 may be application-dependent, but it is generally assumed that the raster compression

1 method 600 selects the lossless representation requiring the fewest number of bits. After the
2 selecting 645, the raster compression method 600 ends 650, indicating completed
3 compression of a data element within the raster stream 212. The raster compression method
4 600 is preferably repeated for each data element within the raster stream 212 and terminates
5 when no more data is presented for compression. Once again, the order of the steps of
6 detecting, extracting, and selecting is given by way of example, and may be conducted in any
7 suitable order.

8 Figure 7 illustrates the operation of the raster packet formatting module 312 in
9 accordance with one embodiment of the present invention. Packet formatting is an optional
10 operation that may be performed in conjunction with the raster compression module 310.

11 The raster packet formatting module 312 is configured to receive sequential iterations of
12 data within the pattern identifier stream 460 and the pattern data stream 470 to provide a
13 packet for use within a packetized raster stream 710. Each packet provided to the packetized
14 raster stream 710 preferably includes a packet header 720 and packet data 730.

15 In the preferred embodiment, the raster packet formatting module 312 is configured
16 to concatenate a fixed number of iterations of elements within the pattern identifier stream
17 460 into the packet header 720 and a corresponding number of iterations of elements within
18 the pattern data stream 470 into the packet data 730. To reduce implementation complexity
19 and increase processing throughput related to processing packets, the fixed number is
20 selected to create a header with a bitwidth equal to the native wordwidth of a processor or
21 hardware subsystem. Figures 9a, 9b, and 9c will be discussed below to explain by way of
22 example the encapsulation of pattern identifiers and pattern data within packets.

23 To maintain proper word boundaries on data within the packetized raster stream 710,
24 the formatted packet may be appended with an arbitrary number of padding bits. The
25 arbitrary number is selected to end the packet at a word boundary and need not be greater
26 than or equal to the native wordwidth of the processor or hardware subsystem. Adding
27

padding bits reduces implementation complexity and increases throughput when processing packets.

In other embodiments, the encodings used within the packet header 720 and the packet data 730 may use statistical information to further compress the raster stream 212.

For example, pattern frequencies may be counted and a form of entropy encoding such as arithmetic encoding or Huffman encoding may be used. The complexity of such encoding schemes may create additional processing burdens counter to one objective of the present invention, nevertheless, entropy encoding and the like may be appropriate in certain embodiments.

Figure 8 illustrates a raster packet formatting method 800, which in one embodiment is a method of operation of the raster packet formatting module 312 of Figure 7. Of course, the method 800 may be conducted independent of the structure of figure 7. The raster packet formatting method 800 starts 805, and receives 810 a pattern. After receiving a pattern including information from the pattern identifier stream 460 and the pattern data stream 470, the method 800 packs 820 the header. In this step, appropriate information is placed into the packet header 720. After packing the header, data from the pattern data stream 470 and in certain embodiments the pattern identifier stream 460 is concatenated 830.

The concatenate step 830 preferably concatenates into the packet data 730 any pattern information not placed within the packet header 720. The distribution of information between the packet header and body may be influenced by the particular application and is left to those skilled in the art. In one embodiment, the data within the pattern identifier stream 460 is packed 820 into the packet header 720 and the data within the pattern data stream 470 is concatenated 830 into the packet data 730. After the concatenate 830 step is completed, an end of block assessment 840 is conducted to verify whether additional data elements can be packed into the packet header 720 and the packet data 730. If so, the method 800 returns to the beginning and continues to loop until the end of a block is reached.

The method 800 then ends 850.

1 Figures 9a, 9b, and 9c illustrate several alternative examples of manners in which
2 the packets within the packetized raster stream 710 may be formatted. Figure 9a shows a
3 sample format that places a header code 910a that is two bits in length within the packet
4 header 720 for each data element encapsulated within a packet. Figures 9b and 9c place
5 header codes 910b and 910c that are a single bit in length within the packet header 720.
6 Figures 9a, 9b, and 9c show examples of data codes 920a, 920b, and 920c placed within the
7 packet data 730 and the corresponding decoded raster data 930a, 930b, and 930c.

8 In the format of Figure 9a, the header code 910a with a value of 00 within the packet
9 header 720 represents a Solid OFF pattern indicating a data element containing all zeros.
10 Likewise, the header code 910a with a value of 01 within the packet header 720 represents
11 a Solid ON pattern indicating a data element containing all ones. In similar fashion, the
12 header code 910a with a value of 10 within the packet header 720 indicates an edge pattern
13 within a data element that has a single transition between ones and zeros. Finally, the header
14 code 910a with a value of 11 indicates verbatim raster data.

15 In contrast to the packet header 720, the number of bits stored within the packet data
16 730 varies according to the pattern as shown in Figure 9a. A solid ON pattern and a solid
17 OFF pattern do not require a data code 920a within the packet data 730. An edge pattern
18 requires one bit within the data code 920a to indicate a transition from zeroes to ones or ones
19 to zeroes, and a sufficient number of additional bits to represent the bit position of the edge
20 transition. In one example with 32 bit data elements, five additional bits are required within
21 the data code 920a. The verbatim data utilizes the same number of bits as the original data
22 element, since that the verbatim word is identical to the original data element.

23 In the format of Figure 9b, the header code 910b that is one bit in length is stored
24 within the packet header for each data element encapsulated within the packet. The header
25 code 910b with a value of 0 corresponds to a solid pattern, while a header code 910b with
26 a value of 1 corresponds to a non-solid (*i.e.* "other") pattern. With a solid pattern, the data
27 code 920b that is a single bit in length within the packet data 730 indicates whether the solid

1 pattern is all zeroes or all ones. With a non-solid pattern, the length of the data code 920b
2 is pattern dependent. A "repeat last data element" option uses a data code 920b that is a
3 single bit in length with a value of 0.

4 In the embodiment depicted in Figure 9b, when representing an edge pattern, the
5 data code 920b begins with a value 10, followed by a bit to indicate a transition to zeros or
6 ones, followed by a sufficient number of additional bits to represent the bit position of the
7 edge transition. In one example using 64 bit data elements, six additional bits are required.
8 Verbatim raster data requires a code of 11 followed by the bits from the original data
9 element.

10 In the format of Figure 9c, the header code 910c that is a single bit in length is stored
11 within the packet header 720 for each data element encapsulated within the packet. A header
12 code 910c with a value of 0 corresponds to a solid pattern, while a value of 1 corresponds
13 to a non-solid pattern (*i.e.* "other" pattern). With a solid pattern, the data code 920c is a
14 single bit in length and indicates whether the solid pattern is all zeros or all ones. With a
15 non-solid pattern, the number of bits within the data code 920c is pattern dependent. With
16 a "repeat data element" option, the data code 920c is a single bit in length with a value of 0.
17 Verbatim raster data requires the data code 920c to begin with a value of 1 followed by the
18 bits from the original data element.

19 The particular embodiment of the raster compression module 310 implied by the
20 format of Figure 9c need only include those modules necessary to generate the supported
21 patterns. As a result, the embodiment implied may have very little complexity in that only
22 solid patterns, verbatim raster data, and an option to repeat the last data element are
23 represented.

24 Figure 10 illustrates the operation of the raster packet deformatting module 318 of
25 Figure 3 in accordance with one embodiment of the present invention. The raster packet
26 deformatting module 318 receives packets from the packetized raster stream 710. In one
27 embodiment, the packets include the packet header 720 and the packet data 730 shown in

1 Figure 7. Multiple iterations of data from the pattern identifier stream 460 and the pattern
2 data stream 470 are encapsulated within the packet header 720 and the packet data 730. The
3 raster packet deformatting module 318 iteratively provides data for the pattern identifier
4 stream 460 and the pattern data stream 470 from each packet within the packetized raster
5 stream 710.

6 In one embodiment, the raster packet deformatting module 318 is configured to
7 unpack from the packet header 720 a fixed number of data elements for the pattern identifier
8 stream 460 and to also unpack from the packet data 730 a related number of data elements
9 for the pattern data stream 470. In some instances, the data within the pattern data stream
10 470 may be null. The fixed number of data elements is preferably selected to create a header
11 with a bitwidth equal to the native wordwidth of a processor or hardware subsystem.

12 In certain embodiments, the encodings used within the packet header 720 and the
13 packet body 730 may include a type of entropy coding such as arithmetic encoding or
14 Huffman encoding. The complexity of such encoding schemes may create additional
15 processing burdens counter to the objectives of the present invention. Nevertheless, entropy
16 encoding and the like may be appropriate in certain embodiments.

17 Figure 11 illustrates a raster packet deformatting method 1100, which may be used
18 as a manner of operation of the raster packet deformatting module 318. Of course, the
19 method 1100 may also be conducted independent of the structure of Figure 10. The raster
20 packet deformatting method 1100 starts 1105 followed by an unpacking 1110 the header .

21 The unpacking 1110, extracts appropriate information from the packet header 720. The
22 unpacking 1110 is followed by unpacking 1120 data which unpacks appropriate information
23 from the packet body 720. The unpacking 1110 and the unpacking 1120 may be adjusted
24 according to the distribution of information between the packet header 720 and the packet
25 data 730 as discussed previously.

26 After extracting the appropriate information, the raster packet deformatting method
27 1100 proceeds to a provide 1130 a pattern, which in one embodiment comprises providing

1 data for the pattern identifier stream 460 and the pattern data stream 470. After the providing
2 1130 is completed, an end of block assessment 1140 ascertains whether additional data
3 elements can be unpacked from the packet header 720 and the packet data 730. If additional
4 data is available, the raster packet deformatting method 1100 loops to the unpack header
5 1110. Otherwise, the raster packet deformatting method 1100 ends 1150.

6 Figure 12 illustrates one embodiment of the raster decompression module 320 of
7 Figure 3. The raster packet deformatting module 318 of Figure 10 may be used in
8 conjunction with the raster decompression module 320. A pattern activation module 1210
9 is configured to receive data from the pattern identifier stream 460 and to provide one or
10 more pattern activation signals 1212. The particular pattern activation signal that is triggered
11 preferably corresponds to data from the pattern identifier stream 460. The pattern activation
12 signals 1212 in turn activate one of the pattern generation modules 1220 or a verbatim data
13 transfer module 1230.

14 In the depicted embodiment, the pattern activation signals 1212 include the solid
15 pattern activation signal 1212a, an edge pattern activation signal 1212b, a half-tone pattern
16 activation signal 1212c, and a verbatim pattern (*i.e.* no detected pattern) activation signal
17 1212d. These signals activate the following modules respectively, a solid pattern generation
18 module 1220a, an edge pattern generation module 1220b, a half-tone pattern generation
19 module 1220c, and the verbatim data transfer module 1230. Upon activation, the pattern
20 generation modules 1220 and the verbatim data transfer module 1230 receive data from the
21 pattern data stream 470 and provide raster data to the raster stream 212.

22 The content of the pattern data stream 470 is dependent upon the pattern identifier
23 stream 460 and corresponds to the module activated by the pattern activation module. In the
24 depicted embodiment, the pattern data stream 470 is directed the solid attribute stream 430a,
25 the edge attribute stream 430b, the half-tone attribute stream 430c, or the verbatim data
26 stream 440. Each of these streams provides data that is a lossless representation of the
27 original raster data. The pattern generation modules and the verbatim data transfer module

1 generate and provide raster data to the raster stream 212 that is identical to the original
2 uncompressed raster data.

3 Figure 13 is a schematic flowchart diagram that illustrates a raster decompression
4 method 1300 that corresponds to the raster decompression module 320. Of course, the
5 method 1300 may be used independent of the particular structure depicted for the raster
6 decompression module 320. Processing starts 1305, followed by an assessment 1310. The
7 assessment 1310 checks whether the data from the pattern identifier stream 460 corresponds
8 to a first pattern. In the depicted embodiment, the first pattern is a solid pattern. The
9 assessment 1310 may be conducted by the pattern activation module 1210. If the data from
10 the pattern identifier stream 460 indicates a solid pattern, the raster compression method
11 proceeds to generate 1312 a solid pattern. Otherwise, the raster decompression module
12 continues to an assessment 1320.

13 The assessment 1320 checks whether the data from pattern identifier stream 460
14 indicates a second pattern which in the depicted embodiment is an edge pattern. If so, the
15 raster decompression method 1300 generates 1322 an edge pattern. Otherwise, the raster
16 decompression method 1300 proceeds to an assessment 1330.

17 The assessment 1330 checks whether the data from pattern identifier stream 460
18 indicates a third pattern which in the depicted embodiment is a half-tone pattern. If so, the
19 raster decompression method 1300 generates 1332 a half-tone pattern. Otherwise, the raster
20 decompression method 1300 proceeds to a transfer 1342 which provides verbatim raster data.

21 The assessments 1310, 1320, and 1330 work together and activate the particular
22 pattern generation that corresponds to the data from the pattern identifier stream 460. It will
23 be obvious to one skilled in the art that other embodiments may provide the required
24 functionality. For example, in some embodiments a jump table or "switch" statement may
25 be used. After the generation 1312, 1322, 1332 or the transfer 1342 is completed, the raster
26 decompression method 1300 ends 1350.
27

1 Figure 14 illustrates a further embodiment of a raster decompression method 1400
2 corresponding to the raster decompression module 320. The raster decompression method
3 1400 starts 1405 and proceeds to an assessment 1410, which checks whether the data from
4 the pattern identifier stream 460 corresponds to verbatim data. If so, the method proceeds
5 to a transfer 1420 which provides verbatim raster data. Otherwise, a codebook is selected
6 1430 as determined by the pattern identifier stream 460.

7 After the codebook is selected 1430, a table lookup 1440 is performed. The table
8 lookup 1440 uses the pattern data 470 as an index into the selected codebook. Given that the
9 bitwidth of the pattern data 470 is dependent on the data from pattern identifier stream 460,
10 the size of the codebook selected may vary. Upon completion of the table lookup 1440 or
11 the transfer 1420, the raster decompression method 1400 ends 1450.

12 The present invention may be embodied in other specific forms without departing
13 from its spirit or essential characteristics. The described embodiments are to be considered
14 in all respects only as illustrative and not restrictive. The scope of the invention is, therefore,
15 indicated by the appended claims rather than by the foregoing description. All changes,
16 which come within the meaning and range of equivalency of the claims, are to be embraced
17 within their scope.

18 What is claimed is:
19
20
21
22
23
24
25
26
27